

Dual Mode Proximity Reader



WAR-EH0-NAB

Dual Technology Proximity Card Reader from WatchNET can read access cards with multiple frequencies and also can be installed using a single or double gang wall box. These readers are compatible with other electronic access control systems by complying with the Wiegand 26-72 bit communication protocol.

Description

The proximity reader is rugged, weather-resistant and slim in design. Blue backlit LED assist operation in low or no light conditions. With the internal sounder, WAR-EH0 provides superior accessibility.

Features

- Elegant & Smooth attractive design
- Green connector or cable for wiring
- Blue LED as normal
- 1 LED with 2 colors and integral sounder for programming and operation
- Multi technology / Dual card format reader

Modulation	ASK at 125 kHz
Maximum read range	100mm (6.00 in.)
Output	W26/34 Options
Operating Voltage	7-12VDC
Operating Current	≤ 100mA
Standby Current	≤ 80mA
Working Temperature	-30°C to 65°C (-22°F to 150°F)
Operating Humidity	0 to 95%
Buzzer Control Input	Dry Contact, Normally Open
LED Control Input	Dry Contact, Normally Open
Dimensions	1.Narrow: 90mm L x 50mm W x 20mm D 2.North America: 115mm L x 70mm W x 25mm D 3.Europe: 115mm L x 95mm W x 25mm D
Weight	200 g



All logos & trade marks represent the registered users only. All rights reserved. All product specifications on this brochure are subject to change without notice.

Division of WatchNET Inc.

WatchNET®

CANADA:

351 Ferrier Street, Unit 5
Markham, ON L3R 5Z2
Toll Free: 1-866-843-6865
Tel: 416-410-6865
Fax: 1-866-331-3341

USA:

171 Cooper Ave. Suite 110
Tonawanda, NY 14150 USA
Toll Free: 1-855-404-3193
Local: 1-716-877-7277
Fax: 1-866-331-3341

info@watchnetaccess.com
www.watchnetaccess.com

INDIA:

RZ- 2, Ground Floor
Kapashera
Opp Kapashera Police Station
New Delhi-110037
Tel/Fax: +91 11 26816005

UAE:

P O Box 126312
No 703, Oxford Towers
Business Bay
Dubai, UAE
Tel: +971 4 2767117